

## LIST OF FIGURES

| <b>Figure No.</b> | <b>Name</b>  | <b>Page</b> |
|-------------------|--|-------------|
| (2.1)             | General overview of industrial electrical power system         | 6           |
| (2.2)             | Existing power system architecture and communication protocols | 7           |
| (2.3)             | Components of SCADA system                                     | 8           |
| (2.4)             | Single SCADA master controlling many substations               | 11          |
| (2.5)             | Typical substation automation architecture                     | 15          |
| (2.6)             | Logical scheme of three levels of substation automation        | 17          |
| (2.7)             | Vertical communication in substation automation system         | 19          |
| (2.8)             | Horizontal communication in substation automation system       | 20          |
| (3.1)             | conventional substation  | 21          |
| (3.2)             | IEC61850 substation automation system according to IEC61850    | 24          |
| (3.3)             | The concept of virtualization                                  | 27          |
| (3.4)             | Virtual and physical entities in 61850                         | 28          |
| (3.5)             | Naming of objects in IEC 61850                                 | 29          |
| (3.6)             | Logical node information categories                            | 31          |
| (3.7)             | Building up of IED devices                                     | 32          |
| (3.8)             | Substation Configuration Language(SCL)                         | 34          |
| (3.9)             | SCL steps to system configuration                              | 36          |
| (3.10)            | Bus network architecture                                       | 38          |
| (3.11)            | Ring network architecture                                      | 39          |
| (3.12)            | Star network architecture                                      | 39          |
| (4.1)             | Conventional communication via hard wiring                     | 43          |
| (4.2)             | Communication via GOOSE  | 44          |
| (4.3)             | IED Server building block                                      | 47          |

|        |  |    |
|--------|--|----|
| (4.4)  | Bay interlocking application                             | 52 |
| (4.5)  | Circuit breaker failure protection                       | 53 |
| (5.1)  | Arc flash detection protection system application        | 58 |
| (5.2)  | Configuration of IED to sense and monitor the arc        | 59 |
| (5.3)  | Feeder single line diagram                               | 60 |
| (5.4)  | Single line diagram (SLD) by SCL                         | 61 |
| (5.5)  | Load feeder SLD by SCL expert                            | 61 |
| (5.6)  | Creating IED_26  | 62 |
| (5.7)  | IED properties dialog box                                | 63 |
| (5.8)  | Logical device (LD) naming                               | 63 |
| (5.9)  | Logical device creation                                  | 64 |
| (5.10) | Creating logical nodes                                   | 65 |
| (5.11) | Mapping the logical node to the IED                      | 66 |
| (5.12) | Assigning IED to logical node and logical node container | 67 |
| (5.13) | Logical node properties                                  | 67 |
| (5.14) | Mapping information in SCD                               | 68 |
| (5.15) | Dataset creation   | 69 |
| (5.16) | Selecting the data attributes forms IED for the data set | 69 |
| (5.17) | GOOSE control block                                      | 70 |
| (5.18) | Transmission of GOOSE message                            | 71 |
| (5.19) | Updating the communication parameter to SCD              | 72 |
| (5.20) | Arc flash detecting protection experiment                | 73 |
| (5.21) | Network testing  | 75 |