

بسم الله الرحمن الرحيم

حَدَّثَكَ لَا (عِلْمَ لَنَا إِلَّا مَا عَلَّمْتَنَا إِنَّكَ أَنْتَ

الْعَلِيمُ الْحَكِيمُ)

صدق الله العظيم

ACKNOWLEDGEMENTS

First of all, I would like to thank ALLAH SWT because for HIS blessing, finally I am able to complete my thesis.

I would like also to thank my supervisor, Dr.AwadallaTaifour Ali for all his teachings and guidance, his criticism on me and my work, and his experience help on this work. It has been a hardship for you, sorry and thank you so much.

My appreciation also to my beloved family especially my mother and my father for all your love, sacrifice, understanding and support, without which, I could never ever walk the first step.

Lastly, my thanks to other colleagues and the persons who directly or indirectly involved and distributed in completing this study and not forget to all my friends who give their full commitment and their best effort. Thank you very much

Abstract

Home automation is very popular nowadays and it is common to read in magazines about its marvels. In its simplest form home automation is the ability to control lighting and household appliances remotely. With this device automation safety from theft, leaking of raw gas and fire is also the most important requirements of home for people. By GSM technology, this study proposes a new solution for

remote home security and device automation system. The proposed system is composed of the GSM module ,device control node and mobile phone. When the temperature sensor detects too high indoor temperature or when the gas sensor detects leakage of gas, the data collecting node will send encoded alarm signal to the users through the GSM module and GSM network immediately. Similarly the user can also control the various devices connected with device control unit through SMS. The SMS received from the user to the device control unit in home. Depends on the SMS received the device control unit will control the corresponding device. This study provides ideal solution to the problems faced by home owners in daily life. The system is wireless therefore more acceptable and cost-effective. The home appliance control system automates various home appliances using SMS. The system uses GSM technology thus providing universally access to the system for automated appliance control.

ملخص البحث

الأتمتة المنزلية تحظى بشعبية كبيرة هذه الأيام، وأنه من الشائع أن تقرأ في المجالات عن الأعاجيب لها. أتمتة المنزل في أبسط شكلها هو القدرة على التحكم في الإضاءة والأجهزة المنزلية عن بعد. مع هذه الأتمتة هناك سلامة للتشغيل الآلي للسرقة، تسرب الغاز الخام والنار وهذه من أهم المتطلبات في المنزل للناس. من خلال تكنولوجيا GSM، يقترح مشروعنا حلاً جديداً لأمن المنزل عن بعد ونظام التشغيل الآلي للأجهزة المنزلية. ويتكون النظام من وحدة GSM ، عقدة التحكم والهاتف المحمول.

مثلا عندما يكتشف جهاز استشعار درجة الحرارة درجة الحرارة في الأماكن المغلقة عالية جدا أو عند استشعار بالكشف عن تسرب غاز ، فإنه سيتم إرسال رسالة قصيرة (التنبيه) إلى المستخدمين من

الايه	i
-------	---

خلال وحدة شبكة GSM فورا. وبالمثل يمكن للمستخدم أيضا التحكم في مختلف الأجهزة المتصلة مع وحدة التحكم في الجهاز من خلال الرسائل القصيرة. وذلك بإرسال SMS من المستخدم إلى وحدة التحكم في الجهاز من خلال نفس شبكة الاستشعار اللاسلكية التي أنشئت في المنزل. ويوفر هذا النظام حلا مثاليا للمشاكل التي يواجهها أصحاب المنازل في الحياة اليومية. لاسلكية نظام أكثر قبولا وفعالة من حيث التكلفة. يستخدم نظام GSM توفير الوصول عالميا إلى نظام لمراقبة الأجهزة الآلية.

Table of Contents

Acknowledgement	ii
Abstract	iii
ملخص البحث	iv
Table of Contents	v
List of Figures	viii
CHAPTER ONE : INTRODUCTION	
1.1	Background 1
1.2	Statement of Problem 1
1.3	Objectives 2
1.4	Methodology 2
1.5	Layout 3
CHAPTER TWO : BACKGROUND AND LITERATURE REVIEW	
2.1	Introduction 4
2.2	Literature Review 4
2.3	Home Automation Elements 6
2.3.1	Sensors 6
2.3.2	Controllers 8
2.3.3	Actuators 10
2.4	Home Automation System Networks 11
2.5	Global System for Mobile Communication (GSM) 12
2.5.1	GSM Architecture 13
2.5.2	GSM Modem 13
2.5.3	HAS Based GSM 14

2.6	AT Command	15
2.7	Benefits of Home Automation	16
CHAPTER THREE: SYSTEM DESIGN		
3.1	System Description	19
3.2	System Operation Flow Diagram	20
3.3	System Components	21
3.3.1	Atmel AVR	21
3.3.2	MAX 232	23
3.3.3	Relay driver IC ULN 2003	23
3.3.4	Relay	24
3.3.5	GSM Modem SIM900	25
CHAPTER FOUR : SOFTWARE CONSIDERATION		
4.1	Introduction	27
4.2	Programming for Home Automation using BASCOMAVR	27
4.3	software programming	27
4.4	Simulation for Home Automation System using labview	35
4.4.1	Labview	35
4.4.2	Design and Simulation	35
4.4.2.1	Fire Alarm System	36
4.4.2.2	Temperature System	37
4.4.2.3	lighting System	38
CHAPTER FIVE :SYSTEM IMPLEMENTATION AND TESTING		

5.1	System Implementation	40
5.2	System Testing	40
5.2.1	Hardware Testing	40
5.2.1.1	power supply testing	41
5.2.1.2	Appliance Interface Test	41
5.2.1.3	5.2.1.3 Serial Unit Test	42
5.2.1.4	GSM Modem Test	42
5.2	Software Testing	43
5.3	RESULT	45
CHAPTER SIX :CONCLUSION AND RECOMMENDATIONS		
6.1	Conclusion	46
6.2	Recommendations	46
REFERENCES		48

List of Figure

Figure	Title	Page
Figure (2.1)	Home Automation elements	6

Figure(2.3)	GSM Architecture	13
Figure (2.4)	GSM modem connection	14
Figure (3.1)	System block diagram	19
Figure (3.2)	System operation flow diagram	20
Figure (3.3)	Figure (3.3) single line diagram of proposed system	21
Figure (3.4)	Pin configurations of microcontroller atmega8	22
Figure (3.5)	MAX 232	23
Figure (3.6)	Schematic Diagram (Each Darlington Pair)	24
Figure (3.7)	ULN2003 Logic Diagram	24
Figure (3.8)	Relay	25
Figure (3.9)	GSM modem SIM900	26
Figure(4.1)	Home automation system LabVIEW Front Panel	36
Figure(4.2)	Home automation system LabVIEW Block Diagram	36
Figure(4.3)	LabVIEW Fire Alarm System Block Diagram	37
Figure(4.4)	Fire Alarm System LabVIEW Front Panel Monitor Screen	37
Figure(4.5)	Block Diagram of Temperature System	38
Figure(4.6)	Temperature System LabVIEW Front Panel	38
Figure(4.7)	Internal Lighting System LabVIEW Block Diagram	39
Figure(4.8)	Internal Lighting System LabVIEW Front Panel	39

Figure(5.1)	Prototype System	40
Figure(5.2)	Power Supply Testing	41
Figure(5.3)	Power Circuit	41
Figure(5.4)	Serial RS232 unit	42
Figure(5.5)	Operation Mode	43
Figure(5.6)	Cheching the code of the program for any erro	43
Figure(5.7)	Compiling the codes of the program	44
Figure(5.8)	The BASCOM program source file in hex format	44