

# DEDICATION

**To my Father,**

**Mother,**

**sisters and Brothers,**

**and colleagues.**

## ACKNOWLEDGMENT

First, of all I am grateful to Almighty Allah For his great blessing. My sincere thanks and gratitude to my Supervisor Dr.Elsadig Al-Mahdi Ahmed, for his encouragement help, guidance and continued support. More thanks to National Municipal Water Corporation. Due thanks are to the staff of the Department of Agricultural Engineering, College of Agricultural Studies, Sudan University of Science and Technology. Deep thanks to my family for their endless patience and continuous support. Thanks are also extended to all those who helped in a way or another to bring this to being.

# TABLE OF CONTENTS

	<b>Contents</b>	<b>Page</b>
	Dedication	I
	Acknowledgment	II
	Table of contents	III
	List of tables	IV
	List of plates	V
	List of figures	VI
	List of abbreviations	VII
	English abstract	IX
	Arabic abstract	X
	<b>Chapter One ( Introduction)</b>	
1.1	Introduction	1
	<b>Chapter Two (Literature Review)</b>	
2.1	Introduction	2
2.2	Irrigation structures	2
2.3	Functions of irrigation structures	3
2.4	Types of flow	3
2.4.1	Free flow	3
2.4.2	Submerged flow	4
2.5	Flow measurement structures	4
2.5.1	Weirs	4
2.5.2	Types of weirs	5
2.5.3	Advantages of weirs	5
2.5.4	Disadvantages of weirs	5
2.6	Classification of weirs according to edge shape	6
2.6.1	Sharp-crested weir	6
2.6.2	Broad-crested weir	8

2.7	Classification of weir according to opening width	8
2.7.1	Suppressed weir	8
2.7.2	Contracted weir	9
2.7.3	V -Notch weir	9
2.8	Discharge measurement equation of the V -Notch weir	9
2.9	Discharge measurement equation of the sluice gates	9
2.9.1	Discharge Formulation	10
2.10	Discharge measurement equation of the combined gate under weir structure	11
2.11	Orifices as flow measurement structures	13
2.11.1	Discharge measurement equation of the orifices	13
2.12	Volume and discharge meters	16
2.12.1	Type of flow meter	16
<b>CHAPTER THREE (Materials &amp; Methods)</b>		
3.1	The study site	19
3.2	Combined weir design	19
3.2.1	Gate design	19
3.2.2	V-Notch weir design	19
3.3	Materials used in the construction of the combined weir	21
3.3.1	Building materials for installation	21
3.3.2	Equipment used in construction	21
3.3.3	Water supply equipment and connectors	21
3.4	Measuring tools and equipments	24
3.5	The experiment equipments	24
3.5.1	Water sources	24
3.5.2	Determination of the gate discharge	24
3.5.3	Volume of water passing through the flow meter	25
3.5.4	Determination of the gate coefficient	25

3.6	Determination of the V- notch weir discharge	25
3.6.1	Volume of water passing through the flow meter	25
3.6.2	Determination of the V- notch weir coefficient	25
3.7	Determination of volume passing through the combined weir	26
3.8	Determination of water volume passing through the flow meter	26
3.9	Determination of discharge coefficient of combined weir	26
3.10	Statistical analysis	27
<b>CHAPTER FOUR (Result and Discussion)</b>		
4.1	Coefficient of gate discharge	29
4.2	Coefficient of weir discharge	30
4.3	Coefficient of discharge for combined weir	31
<b>CHAPTER FIVE</b>		
5.1	Conclusions and Recommendation	34
5.2	References	35
5.3	Appendixes	37

# LIST OF TABLES

	<b>Topic</b>	<b>Page</b>
4.1	Overall average gate operational coefficient for three widths and three heads	29
4.2	Analysis of gate operation coefficient for three widths and three upstream heads	30
4.3	Overall average of V-notch weir coefficient in three different heads	30
4.4	Analysis of weir operation coefficient for three different heads	31
4.5	Overall average coefficient of discharge for combined weir at three different widths and three upstream heads	31
4.6	Analysis of combined weir discharge coefficient under three different widths and three upstream heads	32

# LIST OF PLATES

plates	Topic	Page
2.1	Turbine and paddle wheel flow meters	18
3.1	Combined weir design	22
3.2	Piston pump	22
3.3	Water tank	22
3.4	Flange	22
3.5	Three inch polyethylene pipe	23
3.6	Three inch ball valve	23
3.7	Flow meter connected to pump and tank (3inch)	23

## LIST OF FIGURES

Fig.: No	Topic	page
2.1	Diagrams of various types of weirs used to measure flow rate in an open ditch.	8
2.2	Schematic sketch of a gate operating under free (a) and submerged (b) flow condition	11
2.3	Free discharge	16
2.4	Rectangular orifice	16
3.1	Schematic sketch for combined gate and V-notch ( $90^0$ ) weir	27
3.2	The v- notch weir and gate plate dimensions and lifting screw dimensions	28



## LIST OF ABBREVIATIONS

<b>Symbols</b>	<b>Abbreviations</b>
ASTM	American Society for Testing Material
Av.	Average
b	Gate Opening,
B	The gate width.
C.V.	Coefficient of variation
$C_d$ .	Dimensionless discharge coefficient
Cf.	Coefficient of discharge
Cm	Centimeter
CRBD	Complete randomize block design
D	The gate height. (h)
D/S FSL	Downstream Full Supply level
$E_d$	Downstream specific energy
$E_u$	Upstream specific energy
FSL	Full Supply Level
g	Gravity acceleration
h	Upstream water depth above the notch
H	Head
ISO	International Organization for Standardization
L	Length
M	Mass flow
m	Meter
mm	Millimeter
NSW	Night Storage Weirs
PR	Pipe Regulators
Q	Discharge

$q$	Discharge per unit width of channel,
$Q_{act}$	Total actual discharge.
$Q_g$	Discharge through the gate.
$Q_{theo}$	Total theoretical discharge.
$Q_w$	Discharge through the triangular weir.
Rep	Replication
RSG	Roller Sluice Gate
Sec.	Second
$T_0$	Operating time
U/S FSL	Upstream Full Supply level
USBR	United States bureau of reclamation
$V$	Velocity
$V_{fm}$	Flow meter reading in volume
WHR	Well Head Regulators
$y$	Vertical distance
$y_1$	Upstream depth
$\alpha$	Notch opening angle
$\Theta$	V-notch angle. (Degree)

## ABSTRACT

This study was conducted at the Department of Agricultural Engineering, College of Agricultural Studies (Shambat), Sudan University of Science and Technology (2013-2014).

This study was carried out with objective of testing the stability of coefficients of discharge for locally designed gate and weir operated separately and the coefficient of discharge for both openings operated simultaneously.

The combined rectangular gate under triangular weir was constructed so that the v-notch weir works over the rectangular gate. Three different (7.5, 8.5, 10 cm) gate widths with maximum gate height of 10 cm. The V-notch weir angle is  $90^\circ$ . The combined weir was installed on an open cement-lined-trapezoidal channel.

The stability of the gate coefficient of discharge was tested under three different gate widths (10, 8.5, 7.5cm) each at three different heads (5.5, 4.5, 3.5cm) the result showed the stability of the gate discharge coefficient tested at different gate widths and different heads as there is no significant difference. the coefficient value reported in previous works (0.61) is quite similar to that obtained in the test (0.611)

The v-notch weir (angle  $90^\circ$ ) discharge coefficient was tested under three different heads (7,11,12cm) the results showed no significant difference. The coefficient values reported in previous works (0.53) and those obtained in the test (0.55).

The combined weir coefficient of discharge is (0.502).is quite stable as proved by statistical analysis

The combined gate under v-notch weir coefficient of discharge reported in previous works is (0.694, 0.691 and 0.665) for weir angles ( $30^{\circ}$ ,  $45^{\circ}$ ,  $60^{\circ}$ ) respectively. Showing the decrease in coefficient value with the increase of v-notch angle, so the coefficient of discharge value (0.502) obtained in the test compares very well.

From the above result it could be concluded that a gate under v-notch weir  $90^{\circ}$  can be designed and constructed locally to measure discharge in open channels with high reliability.

## الخلاصة

أجريت هذه الدراسة في قسم الهندسة الزراعية كلية الدراسات الزراعية (شبات) جامعة السودان للعلوم والتكنولوجيا (2013 - 2014).

هذه الدراسة تهدف الى اختبار استقرار معامل التصرف للبوابة المنزقة والهدار المثلي المصمم محليا كل علي حدة ومعامل التصرف لهما بالهدار المركب.

صممت البوابة المستطيلة تحت الهدار المثلي ذو الزاوية  $90^0$  بثلاثة ابعاد مختلفة للعرض وهي (10, 8.5, 7.5 سم) تم تركيب البوابة المركبة علي القناة المفتوحة المبطنه بالاسمنت ذات المقطع شبه المنحرف.

تم اختبار استقرار معامل التصرف للبوابة بثلاثة ابعاد مختلفة لعرض الفتحة وهي (10, 8.5, 7.5 سم) وثلاثة ضواغط مختلفة (3.5, 4.5, 5.5 سم) عند تحليل التباين اظهرت النتائج عدم وجود فروقات معنوية بين قيمة معامل التصرف في الفتحات والضواغط المختلفة . في ادبيات البحوث السابقة (0.61) والقيمه التي تم الحصول عليها في التجربة (0.611). مما يظهر تطابقا في القيمة .

تم اختبار استقرار معامل التصرف للهدار المثلي ذو الزاوية  $90^0$  عند ثلاثة ضواغط مختلفة وهي (7, 11, 12 سم) عند تحليل التباين اظهرت النتائج عدم وجود فروقات معنوية بين قيمة معامل التصرف في التجربة. ادبيات البحوث السابقة (0.53) والقيمة التي تم الحصول عليها في التجربة (0.502).

أظهرت التجربة استقرارا لمعامل التصرف للبوابة المركبة وذلك حسب نتائج تحليل التباين.

قيمة معامل التصرف للبوابة المركبة تحت الهدار المثلي في الادبيات السابقة للبحوث هي (0.665, 0.691, 0.694) عند الزوايا ( $30^0, 45^0, 60^0$ ) علي التوالي. وتوضح بان قيمة معامل التصرف تقل بزيادة زاوية الهدار المثلي , وعليه قيمة معامل التصرف التي تم الحصول عليها في التجربة (0.502) عند زاوية الهدار  $90^0$  وهي تظهر مقارنة جيدة.

من النتائج أعلاه يمكن ان نخلص الى أن البوابة المركبة تحت هدار مثلي ذو الزاوية  $90^0$  يمكن تصميمها وتنفيذها محليا لقياس التصرف في القنوات المفتوحة وتعطي نتائج ذات اعتمادية عالية.