

		DC		EV	EH				WA	L.S	L.L	COM 1	COM 2	COM 3
					EHa		EHb							
		DCa	DCb		max	min	max	min						
Load		7.2	25.9	9.27	4.5	2.25	29.7	14.85	29.43	7.38				
B 1	M	5.38	1.63	6.92	-1.70	-0.85	-5.07	-2.54	5.03	-2.78	11.52	48.33	47.12	-2.22
	N	0	0	0	6.75	3.38	14.87	7.44	-14.74	11.07	0	48.88	-5.46	50.01
A 2	M	-2.72	1.63	-3.50	-1.70	-0.85	-5.07	-2.54	5.03	-2.78	-26.88	-58.59	-42.00	-18.44
	N	0	0	0	-6.75	-3.38	14.87	7.44	-14.74	-11.07	0	-7.86	-11.26	-7.86
	V	10.8	0	13.91	0	0	0	0	0	0	64	181.4 4	181.4 4	21.64
A 3	M	-2.72	1.63	-3.50	-1.70	-0.85	-5.07	-2.54	5.03	-2.78	-26.88	-58.59	-42.00	-18.44
	N	10.8	0	13.91	0	0	0	0	0	0	64	181.4 4	181.4 4	21.64
	V	0	0	0	-6.75	-3.38	- 14.87	-7.44	14.74	-11.07	0	-50.01	-9.54	-58.72
E 4	M	-2.72	-3.26	-3.50	3.36	1.68	11.49	5.74	-11.38	5.51	-12.48	10.61	-46.32	22.31
	N	10.8	12.95	13.91	0	0	0	0	0	0	64	197.6 3	197.6 3	33.29
D 5	M	-2.72	-0.31	-3.50	-1.70	-0.85	-6.15	-3.07	6.09	-2.78	-8.64	-44.66	-25.94	-21.72
	N	10.8	25.9	13.91	0	0	29.67	14.83	-29.40	0	64	255.8 7	197.1 3	87.01
	V	0	0	0	6.75	3.38	0	0	0	11.07	0	28.94	2.89	28.94
D 6	M	-2.72	-8.08	-3.50	-1.70	-0.85	-6.15	-3.07	6.09	-2.78	-8.64	-54.37	-30.06	-28.71
	N	0	0	0	6.75	3.38	0	0	0	11.07	0	28.94	2.89	28.94
	V	-10.8	- 26.42	- 13.91	0	0	29.67	14.83	-29.40	0	-64	- 183.3 8	231.1 6	-3.36
C 7	M	5.38	11.34	6.92	-1.70	-0.85	-6.15	-3.07	6.09	-2.78	21.12	63.51	82.23	4.98
	N	0	0	0	6.75	3.38	29.67	14.83	-29.40	11.07	0	70.99	-13.79	70.99