

Dedication

*To my father from whom I learned the meaning of life,
work and knowledge*

*To my beloved mother whose patience and love is my
stock of life*

To my wife the meaning of life

To my daughter

To My sister & brothers

To My friends

And all of you

I present my humble gift

This research

Acknowledgement

I would like to thank all those who devoted their efforts to help me in this thesis, I am grateful to any one who participated with his knowledge, time and ideas.

My Special Thanks to Ustaz: Khamis Arbeesh Saad Eldin, who supervised this research from its beginning till it reached its final form.

My Thanks to the Staff of Sudan University Of Science and Technology and to the Staff of Khartoum North power station for their invaluable help.

Abstract

Power factor is considered as a basic factor in the AC power systems. Due to that most of recent studies concentrate on power factor control by designing circuits of control systems so as to conserve the level of it.

This research is a study of power factor control circuit card in generation systems by using the software simulation program (Orcad p-spice) to realize the actual result of the controller of power factor by the computer program, for the following reasons:

First, the faults which occur in the power factor control cards, due to the dust and heat in Sudan atmosphere. If one component of the card is damaged, the card should be replaced by a new one which is not available locally. These cards cost much money and time. Second, to encourage the local industries to design and reprint the electronic Circuits in the printed circuit boards (PCB).

المستخلص

يعتبر معامل القدرة عامل أساسي في أنظمة القدرة، ونسبة لأهميته اتجهت معظم الدراسات في الآونة الأخيرة بالاهتمام به وذلك عن طريق تصميم دوائر تحكم تعني بالتحكم بمعامل القدرة.

ولقد تم اختيار هذا البحث المتعلق بدراسة التحكم في معامل القدرة لعدة أسباب:

أولاً: الأعطال المتعلقة بـ (كثرت التحكم في معامل القدرة) بسبب الغبار وارتفاع درجات الحرارة، فإذا تعطلت إحدى مكونات الكرت يتم استبدال الكرت كاملاً بكرت جديد وهو غير متاح محلياً واستجلاية من الخارج يكلف الكثير من الوقت والمال.

ثانياً: تشجيع الصناعة المحلية بتصميم وطباعة الدوائر الالكترونية.

وفي هذا البحث تم تصميم دائرة تحكم في نظام التوليد للتحكم في معامل القدرة وجعله في مستوي مناسب و فعال، ولكن تعذرت طباعة الكرت في لوحة التحكم وذلك لان بعض مكونات الكرت غير متوفرة محلياً.

Contents

Dedication.....	I
Acknowledgement	II
Abstract	III
المستخلص	V
Contents	VII
Table of figures	X
Chapter one: Introduction	
1.1 Energy Efficiency.....	1
1.2 Power Factor.....	1
1.3 Improving Power Factor.....	4
1.4 Scope of the work	5
Chapter two: power stations and excitation system	
2.1 Introduction	6
2.2 Thermal power stations.....	6
2.3 Classification of thermal power plant	7
2.3.1 Fuel Power plant	7
2.3.2 Prime mover Power plant	7
2.4 Cooling towers and waste heat	8
2.5 Other sources of energy	10
2.5.1 Hydroelectricity	10
2.5.2 Pumped storage	10
2.5.3 Solar	10
2.5.4 Wind	11
2.6 Synchronous generators	11
2.7Excitation system.....	13
2.7.1 Basic function of Excitation system.....	13
2.7.2 Elements of excitation system.....	13
2.7.3Type of excitation systems.....	15
Chapter three: Reactive power and the methods of voltage control	
3.1 Definition of Reactive power.....	26
3.2 Sources of reactive.....	26
3.2.1 Synchronous generators.....	26
3.2.2 Synchronous compensators.....	27
3.2.3 Capacitive and inductive compensators.....	27

3.2.4 Over head lines and underground cables.....	27
3.2.5 Transformer.....	28
3.3 methods of voltage control.....	28
3.3.1 Shunt reactors.....	29
3.3.2 Shunt capacitors.....	29
3.3.3 Synchronous condensers.....	30
3.3.4 Static VAR compensators.....	31
3.3.5 Thyristor-switched capacitor (TSC).....	31
Chapter Four: Operation of Power factor control	
4.1 specifications	35
4.1.1 Range of control	35
4.1.2 Accuracy of power factor control.....	35
4.1.3 Accuracy of reactive current control.....	36
4.1.4 Temperature range.....	36
4.1.5 Input signals.....	36
4.1.6 Operation indication.....	36
4.1.7 Mode selection.....	37
4.1.8 Remote level control.....	37
4.2 Description of operation.....	37
4.2.1 CMOS QUAD solid state switch (4016, IC1, IC2).....	37
4.3 Result.....	41
4.4 discussion.....	47
Chapter Five: Conclusion and Recommendation	
5.1 Conclusion	48
5.2 Recommendation.....	49
Reference.....	50

Table of figure:

Figure	Title	Page
Figure 1.1	power triangle	2
Figure 1.2	power factor at 200kw	4
Figure 2.1	synchronous generator excitation control system	13
Figure 2.2	Dc excitation system with amplidyne voltage regulator	16
Figure2.3	field controlled alternator rectifier excitation system	19
Figure 2.4	alternator supplied controlled rectifier excitation system	19
Figure 2.5	brushless excitation system	21
Figure 2.6	potential source controlled rectifier excitation system	22

Figure 2.7	compound source rectifier excitaion system	23
Figure 2.8	Generrex compound controlled rectifier	25
Figure 3.1	Thyristor-switched capacitor(TSC)	32
Figure 3.2	switch operation of a TSC	33
Figure 3.3	TSC scheme	34
Figure 4.1	Power factor control circuit	40
Figure 4.2	Circuit implementation of power factor control card	42
Figure 4.3	The out put voltage at Tp5 becomes negative	43
Figure 4.4	The out put voltage at Tp5 becomes positive	44
Figure 4.5	The out put voltage at tp5 at the optimum position	45
Figure 4.6	The Angles with out put of the Tp5	46

Table of tables

Table No.	Name	Page
Table 4.1	The Angles with out put of the Tp5	46